



Właz prostokątny

Standard with EPDM gasket G/1500 and s.s. handle VI/165/A.
Gasket on cover not glued.
AISI 304L-14307 / AISI 316L-14404

1700

555x432mm

Standard z uszczelką EPDM G / 1500 i s.s. Uchwyt VI / 165 / A.
Uszczelka na pokrywie nie klejonej.
AISI 304L-14307 / AISI 316L-14404



Model	Mat.	Kołnierz		Pokrywa	P.max	Waga
		Wysokość	Grubość	Grubość		
	AISI	mm	mm	mm	bar	kg
1700	304L	60	12,0	3,0	1,0	23
1701	304L	80	12,0	3,0	1,0	22
1702	304L	100	12,0	3,0	1,0	28
1700/B	316/L	60	12,0	3,0	1,0	23
1701/B	316/L	80	12,0	3,0	1,0	22
1702/B	316/L	100	12,0	3,0	1,0	28

Dostępne uszczelki			
Art. nr	Material	Kolor	Temp.
96420	NBR	Biały RAL9016	-30°/ 110°C
96421	EPDM	Siwy RAL7040	-15°/ 90°C
96425	SILIKON	Transparentny	-50°/200°C
96426	FKM	Czarny RAL 9017	-10°/ 250°C

