



Upper lid D26E (Without / bez PED)

Upper circular pressure manhole economic type fitted with sodalime 6mm thick glass cover outwardly opening
AISI 304 o AISI 316/L
– access 400 - 450 - 500 - 600 mm.

Tailored height on request

Standard handweel: nylon handwheel (vlt1609004)

Standard gasket: silicone

Standard surface finish: satin cover/satin frame

Standard glass: sodalime tempered glass for use up to 150°C

Standardowe pokrętki: z tworzywa sztucznego (vlt1609004)

Standardowa uszczelka: silikon

Standardowe wykończenie powierzchni: pierścień satynowany/kołnierz satynowany

Standardowe szkło: Sodowowapienne # 6,0 mm do stosowania w temperaturze do 150°C

ALTERNATYWNIENIE NA ŻĄDANIE: szkło odpowiednie do wyższych temperatur, szkło poliwęglanowe.



A	400	450	500	600
B	4	4	4	6
Ciśnienie	-1/+3 Bar	-1/+3 Bar	-1/+2 Bar	-1/+2 Bar
Waga	+/- kg	+/- kg	+/- kg	+/- kg

Available gaskets	
TYPE OF MATERIAL	TEMPERATURE
EPDM	-35°/+110°
NITRILE (NBR)	-15°/+110°
SILICON	-35°/+200°
VITON	-20°/+200°
FEP-Silicone	-60°/+204°
FEP-Viton	-60°/+204°

