





Uszczelki włączów serii ST-Z




Art. nr	Material	Kolor	Temp.
96210	NBR	Biały/Whita RAL9016	-30°/ 110°C
96211	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96215	SILIKON	Transparentny/Biały	-50°/200°C
96216	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włączów :
Mod. 170
Mod. 174/AE
Mod. 180
Mod. 14/L




Art. nr	Material	Kolor	Temp.
96000	NBR	Biały/Whita RAL9016	-30°/ 110°C
96001	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96005	SILIKON	Transparentny/Biały	-50°/200°C
96006	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włączów :
Mod. 200
Mod. 190 wersja do 29-02-2017



Art. nr	Material	Kolor	Temp.
96460	NBR	Biały/Whita RAL9016	-30°/ 110°C
96461	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96465	SILIKON	Transparentny/Biały	-50°/200°C
96466	FPM/VITON	Czarny RAL 9017	-10°/ 250°C


Do włączów :
Mod. 191
Mod. 190 wersja od 01-03-2017



Art. nr	Material	Kolor	Temp.
96040	NBR	Biały/Whita RAL9016	-30°/ 110°C
96041	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96045	SILIKON	Transparentny/Biały	-50°/200°C
96046	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włączów :
Mod. 200LZD
Mod. 200LZD/C


Mod. G/200PES



Art. nr	Material	Kolor	Temp.
96450	NBR	Biały/Whita RAL9016	-30°/ 110°C
96451	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96455	SILIKON	Transparentny/Biały	-50°/200°C
96456	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włączów :
Mod. 200PES
Mod. 200PES snodo


Mod. G/630



Art. nr	Material	Kolor	Temp.
96490	NBR	Biały/Whita RAL9016	-30°/ 110°C
96491	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96495	SILIKON	Transparentny/Biały	-50°/200°C
96496	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włączów :
Mod. 630


Mod.



Art. nr	Material	Kolor	Temp.
96050	NBR	Biały/Whita RAL9016	-30°/ 110°C
96051	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96055	SILIKON	Transparentny/Biały	-50°/200°C
96056	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włączów :
Mod. 200R


Mod. G/200RP



Art. nr	Material	Kolor	Temp.
96230	NBR	Biały/Whita RAL9016	-30°/ 110°C
96231	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96235	SILIKON	Transparentny/Biały	-50°/200°C
96236	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włączów :
Mod. 200RP

Mod. G/Z175




Art. nr	Material	Kolor	Temp.
96180	NBR	Biały/Whita RAL9016	-30°/ 110°C
96181	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96185	SILIKON	Transparentny/Biały	-50°/200°C
96186	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włączów :
Mod. Z175

Uszczelki włazów serii ST-Z


Mod. G/1500



Art. nr	Material	Kolor	Temp.
96420	NBR	Biały/Whita RAL9016	-30°/ 110°C
96421	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96425	SILIKON	Transparentny/Biały	-50°/200°C
96426	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włazów :
Mod. 1500 / 1400
Mod. 1500/AL
Mod. 1600
Mod. 1700


Mod. G/295



Art. nr	Material	Kolor	Temp.
96020	NBR	Biały/Whita RAL9016	-30°/ 110°C
96021	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96025	SILIKON	Transparentny/Biały	-50°/200°C
96026	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włazów :
Mod. 285
Mod. 295


Mod. G/R165



Art. nr	Material	Kolor	Temp.
96200	NBR	Biały/Whita RAL9016	-30°/ 110°C
96201	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96205	SILIKON	Transparentny/Biały	-50°/200°C
96206	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włazów :
Mod. 160
Mod. 165
Mod. 160/2B


Mod. G/P200



Art. nr	Material	Kolor	Temp.
96100	NBR	Biały/Whita RAL9016	-30°/ 110°C
96101	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96105	SILIKON	Transparentny/Biały	-50°/200°C
96106	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włazów :
Mod. 230
Mod. 235
Mod. 60


Mod. G/AE



Art. nr	Material	Kolor	Temp.
96410	NBR	Biały/Whita RAL9016	-30°/ 110°C
96411	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96415	SILIKON	Transparentny/Biały	-50°/200°C
96416	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włazów :		
Mod. 220	Mod. 50	Mod. N/100
Mod.250	Mod. 90	Mod. N/250
Mod. 255	Mod. 100	Mod. C/330
	Mod. 110	Mod. 220/E


Mod. G/TR300



Art. nr	Material	Kolor	Temp.
96470	NBR	Biały/Whita RAL9016	-30°/ 110°C
96471	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96475	SILIKON	Transparentny/Biały	-50°/200°C
96476	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włazów :	
Mod. 210	Mod. 70
Mod. 215	Mod. 80
Mod. 240	
Mod. 245	


Mod. G/TR500



Art. nr	Material	Kolor	Temp.
96170	NBR	Biały/Whita RAL9016	-30°/ 110°C
96171	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96175	SILIKON	Transparentny/Biały	-50°/200°C
96176	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włazów :	
Mod. 520	Mod. 150
Mod. 270	Mod. N/150
Mod. N270	
Mod. 275	


Mod. G/6V250



Art. nr	Material	Kolor	Temp.
960	NBR	Biały/Whita RAL9016	-30°/ 110°C
961	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
965	SILIKON	Transparentny/Biały	-50°/200°C
966	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włazów :
Mod. 6V/250

Mod. G/NL250




Art. nr	Material	Kolor	Temp.
96220	NBR	Biały/Whita RAL9016	-30°/ 110°C
96221	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96225	SILIKON	Transparentny/Biały	-50°/200°C
96226	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włazów :
Mod. N/240/4V
Mod. N/240
Mod. NL/250

Uszczelki włazów serii ST-Z


Mod. G/400AZ/NL



Art. nr	Material	Kolor	Temp.
96430	NBR	Biały/Whita RAL9016	-30°/ 110°C
96431	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96435	SILIKON	Transparentny/Biały	-50°/200°C
96436	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włazów :
Mod. 400/AZ-NL


Mod. G/T



Art. nr	Material	Kolor	Temp.
96330	NBR	Biały/Whita RAL9016	-30°/ 110°C
96331	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96335	SILIKON	Transparentny/Biały	-50°/200°C
96336	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włazów :
Mod. 400/AZ-GN


Mod. G/T200



Art. nr	Material	Kolor	Temp.
96360	NBR	Biały/Whita RAL9016	-30°/ 110°C
96361	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96365	SILIKON	Transparentny/Biały	-50°/200°C
96366	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włazów :
Mod. N/230
Mod. T1/200
Mod. 3V/200


Mod. G/T300



Art. nr	Material	Kolor	Temp.
96300	NBR	Biały/Whita RAL9016	-30°/ 110°C
96301	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96305	SILIKON	Transparentny/Biały	-50°/200°C
96306	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włazów :
Mod. T1/300
Mod. 3V/300


Mod. G/T400



Art. nr	Material	Kolor	Temp.
96370	NBR	Biały/Whita RAL9016	-30°/ 110°C
96371	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96375	SILIKON	Transparentny/Biały	-50°/200°C
96376	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włazów :
Mod. T1/400
Mod. 3V/400
Mod. TV/400
Mod. T1/G400


Mod. G/T450



Art. nr	Material	Kolor	Temp.
96380	NBR	Biały/Whita RAL9016	-30°/ 110°C
96381	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96385	SILIKON	Transparentny/Biały	-50°/200°C
96386	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włazów :
Mod. T1/450, T1/G450
Mod. 5V/450
Mod. TV/450
Mod. T/450


Mod. G/T500



Art. nr	Material	Kolor	Temp.
96310	NBR	Biały/Whita RAL9016	-30°/ 110°C
96311	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96315	SILIKON	Transparentny/Biały	-50°/200°C
96316	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włazów :
Mod. T1/500, T1/G500
Mod. 6V/500
Mod. TV/500
Mod. T/500


Mod. G/T600



Art. nr	Material	Kolor	Temp.
96320	NBR	Biały/Whita RAL9016	-30°/ 110°C
96321	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96325	SILIKON	Transparentny/Biały	-50°/200°C
96326	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włazów :
Mod. T1/600
Mod. 8V/600
Mod. TV/600
Mod. T/600

Mod. G/T800




Art. nr	Material	Kolor	Temp.
96350	NBR	Biały/Whita RAL9016	-30°/ 110°C
96351	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96355	SILIKON	Transparentny/Biały	-50°/200°C
96356	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włazów :
Mod. T1/800
Mod. 10V/800

Uszczelki włazów serii ST-Z


Mod. G/300/P



Art. nr	Material	Kolor	Temp.
96600	NBR	Biały/Whita RAL9016	-30°/ 110°C
96601	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96605	SILIKON	Transparentny/Biały	-50°/200°C
96606	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włazów :
Mod. 300L
Mod. 300P


Mod. G/400P



Art. nr	Material	Kolor	Temp.
96250	NBR	Biały/Whita RAL9016	-30°/ 110°C
96251	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96255	SILIKON	Transparentny/Biały	-50°/200°C
96256	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włazów :
Mod. 400L
Mod. 400P


Mod. G/450P



Art. nr	Material	Kolor	Temp.
96260	NBR	Biały/Whita RAL9016	-30°/ 110°C
96261	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96265	SILIKON	Transparentny/Biały	-50°/200°C
96266	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włazów :
Mod. 450L
Mod. 450P


Mod. G/500P



Art. nr	Material	Kolor	Temp.
96270	NBR	Biały/Whita RAL9016	-30°/ 110°C
96271	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96275	SILIKON	Transparentny/Biały	-50°/200°C
96276	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włazów :
Mod. 500L
Mod. 500P

Mod. G/600P



Art. nr	Material	Kolor	Temp.
96280	NBR	Biały/Whita RAL9016	-30°/ 110°C
96281	EPDM	Siwy/Grey RAL7040	-15°/ 90°C
96285	SILIKON	Transparentny/Biały	-50°/200°C
96286	FPM/VITON	Czarny RAL 9017	-10°/ 250°C

Do włazów :
Mod. 600L
Mod. 600P